

ILS or LOC RWY 3

LOC/DME I-AEZ 108.5 Chan 22 APCH CRS 029° TDZE 685 Arpt Elev 690 [USA] WHEELER-SACK AAF (FORT DRUM) (KGTB)

DME or RADAR required. RADAR required for procedure entry.

*** When ALS inop, increase vis to ½ mile.
 ** When ALS inop, increase CAT A vis to 1 mile, CAT B vis to 1¼ miles, CAT C vis to 2½ miles, CAT D vis to 3¼ miles, CAT E vis to 3 miles.

ATIS 119.525 APP CON 124.875 307.125 TOWER 118.75 290.25 GND CON 123.65 229.8 ASR/PAR

*** When ALS inop, increase CAT AB vis to 1 mile; CAT C vis to 1½ miles; CAT D vis to 1¼ miles; CAT E vis to 1½ miles.
 *** Circling NA E of Rwy 21 and 33.
 Circling NA for CAT BCD to Rwy 8.
 Circling NA for CAT E to Rwy 8-26 and 15-33.

LOCALIZER 108.5 I-AEZ Chan 22
 WATERTOWN 109.8 ART Chan 35
 JOGIN I-AEZ 18 RADAR 5000
 KIMBO I-AEZ 8.5 RADAR
 REMIE I-AEZ 4.3 RADAR
 I-AEZ 2.6
 I-AEZ 1.6

ALSF-1 (A1)

MISSED APPROACH: Climb to 1200, then climbing left turn to 5000 direct ART VORTAC and hold. Continue climb-in-hold to 5000.

ALTERNATE MISSED APPROACH: When directed by ATC, climb to 1200, then climbing left turn to 3000 via hdg 340° within 10 NM (RADAR required).

GS 3.00° TCH 66

CATEGORY	A	B	C	D	E
S-ILS 3 *	957-½ 272 (300-½)				
S-LOC 3 **	1560-½ 875 (900-½)	1560-¾ 875 (900-¾)	1560-2 875 (900-2)	1560-2¼ 875 (900-2¼)	1560-2½ 875 (900-2½)
CIRCLING ****	1560-1¼ 870 (900-1¼) 1560-2½ 870 (900-2½) 1560-2¾ 870 (900-2¾) 1640-3 950 (1000-3)				

DME MINIMUMS

S-LOC 3 ***	1080-½ 395 (400-½)	1080-¾ 395 (400-¾)	1080-1 395 (400-1)
CIRCLING ****	1200-1 510 (600-1)	1220-1½ 530 (600-1½)	1380-2¼ 690 (700-2¼)

1080-1 395 (400-1) 1640-3 950 (1000-3)

FAF to MAP 6.9 NM

Knots	60	90	120	150	180
Min:Sec	6:54	4:36	3:27	2:46	2:11

FORT DRUM, NEW YORK

44° 03'N-75° 43'W

WHEELER-SACK AAF (FORT DRUM) (KGTB)

ILS or LOC RWY 3

NE-2, 01 OCT 2026 to 29 OCT 2026

NE-2, 01 OCT 2026 to 29 OCT 2026