

WAAS CH 49200 W12A	APP CRS 116°	Rwy Ldg TDZE Apt Elev	4001 193 194
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 12

TRACY MUNI (TCY)

RNP APCH - GPS.

▼

Rwy 12 helicopter visibility reduction below ¾ SM NA. Circling NA southwest of Rwy 12-30.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using SCK altimeter setting. When local altimeter setting not received, use SCK altimeter setting and increase LPV DA to 503 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 507 feet and all visibilities ½ SM. Increase all MDAs 60 feet and LNAV visibility Cat C ½ SM.

MISSED APPROACH:
Climb to 700 then climbing left turn to 3200 direct HAIRE and hold, continue climb-in-hold to 3200.

AWOS-3 118.375	NORCAL APP CON 123.85 278.3	UNICOM 123.075 (CTAF) 0
--------------------------	---------------------------------------	--

Enroute chart for RNP APCH to RWY 12. The chart shows the following features:

- Holding Pattern:** 6000/3100 HOLD, 4 NM, 116°/296°.
- Altitudes:** 3100 NoPT 066° (5.3), 2000, 194 (ELEV), 193 (TDZE).
- Distances:** 4 NM, 3.7 NM, 0.9 NM, 1 NM.
- Waypoints:** (IAF) ALTAM, (IF/IAF) OYOSO, (FAF) JENEG, ZOTPI 1.9 NM to RW12, RW12 271.
- Obstacles:** SUNOL 4000 017° (115.5), R-2531.
- MSA:** MSA RW12 25 NM, 5600.
- Procedure:** Procedure NA for arrivals at ALTAM on V334-392 southbound.

4 NM Holding Pattern		OYOSO	JENEG	ZOTPI 1.9 NM to RW12	HAIRE
6000 ← 296°		2000	820	1 NM to RW12	△
3100 → 116°					
GP 3.00°					
TCH 41					
		6.6 NM	3.7 NM	0.9 NM	1 NM
CATEGORY	A	B	C	D	
LPV DA	443-¾	250 (300-¾)		NA	
LNAV/VNAV DA	447-¾	254 (300-¾)		NA	
LNAV MDA	540-1	347 (400-1)		NA	
CIRCLING	580-1 386 (400-1)	660-1 466 (500-1)	660-1½ 466 (500-1½)	NA	

ELEV 194 TDZE 193

MIRL Rwy 8-26 and 12-30 **0**
REIL Rwy 8, 12, 26 and 30 **0**

TRACY, CALIFORNIA

Amtdt 2C 11JUN26

37°41'N-121°26'W

TRACY MUNI (TCY)

RNAV (GPS) RWY 12