


WAAS CH 40127 W13A	APP CRS 131°	Rwy Ldg 5107 TDZE 45 Apt Elev 45
--	------------------------	---

RNAV (GPS) RWY 13
BAY CITY RGNL (BYY)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Rwy 13, 31 helicopter visibility reduction below 1 SM NA. RADAR required. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Palacios altimeter setting and increase all DA 63 feet and all MDA 80 feet; increase LNAV visibility Cat C ¼ mile. VDP and Baro-VNAV N/A when using Palacios altimeter setting.

MISSED APPROACH:
Climb to 2000 direct
LEMUR and hold.

AWOS-3PT 118.075	HOUSTON CENTER 128.6 360.8	UNICOM 122.8 (CTAF) 0
----------------------------	--------------------------------------	---------------------------------



4 NM Holding Pattern

2000 ← 311°

GP 3.00° TCH 45

COSDI

JORUM 1700

CIGAM 2.4 NM to RW13

*LNAV only.

*0.8 NM to RW13

RW13

6.6 NM 2.7 NM 1.6 0.8

CATEGORY	A	B	C	D
LPV DA	295-1	250 (300-1)		NA
LNAV/VNAV DA	295-1	250 (300-1)		NA
LNAV MDA	460-1	415 (500-1)	460-1½ 415 (500-1½)	NA
CIRCLING	500-1	455 (500-1)	620-1½ 575 (600-1½)	NA

ELEV 45 TDZE 45

131°

5107 X75

REIL Rwy 13 and 31 0

MIRL Rwy 13-31 0

SC-5, 01 OCT 2026 to 29 OCT 2026

SC-5, 01 OCT 2026 to 29 OCT 2026