

WAAS CH 53727 W08A	APP CRS 081°	Rwy Ldg TDZE Apt Elev	5003 201 201
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 8

BAXLEY MUNI (BHC)

RNP APCH-GPS.


▼

▲ NA

Baro-VNAV NA when using Alma altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Alma altimeter setting: increase LPV DA to 513 feet; increase LNAV/VNAV DA to 515 feet; increase all MDAs 40 feet and visibility Cat C ¼ SM and visibility Cat D ¼ SM. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 1200 then
climbing right turn
to 2300 direct
KIVEC and hold.

AWOS-3PT 118.2	JACKSONVILLE CENTER 127.575 269.025	UNICOM 122.8 (CTAF) 0
--------------------------	---	--



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).		1200	2300	KIVEC
2300 ← 261°		081° →		1800	1020	* LNAV only.
GP 3.00° TCH 59		6.9 NM		2.4 NM	2.4 NM	
CATEGORY	A	B	C	D		
LPV DA		484-1	283 (300-1)			
LNAV/VNAV DA		486-1	285 (300-1)			
LNAV MDA		560-1	359 (400-1)			
CIRCLING	620-1 419 (500-1)	700-1 499 (500-1)	700-1½ 499 (500-1½)	1060-2¾ 859 (900-2¾)		

