

WAAS CH 63035 W19A	APP CRS 189°	Rwy Ldg 5007 TDZE 497 Apt Elev 499
--	------------------------	---


RNAV (GPS) RWY 19

WILLIAM L WHITEHURST FLD (M08)


T DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson altimeter setting and increase all MDA 80 feet, increase LP
A NA Cats C/D visibilities $\frac{1}{4}$ mile, increase LNAV Cats C/D visibilities $\frac{1}{8}$ mile and Circling Cats C/D visibilities $\frac{1}{4}$ mile. Rwy 19 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Rwy 1 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 2500
direct LOHNI and hold.

AWOS-3 121.125	MEMPHIS CENTER 124.35 318.1	UNICOM 123.0 (CTAF)
--------------------------	---------------------------------------	-------------------------------




ELEV 499		TDZE 497
----------	--	----------



MIRL Rwy 1-19
REIL Rwy 1 and 19


MISSED APCH FIX



2500	LOHNI
	

Visual Segment - Obstacles.

HESKA 4 NM Holding Pattern



	1.6 NM	3 NM	6 NM	
CATEGORY	A	B	C	D
LP MDA	840-1 343 (400-1)			
LNAV MDA	920-1 423 (500-1)	920-1¼ 423 (500-1¼)		
CIRCLING	980-1 481 (500-1)	1100-1¾ 601 (700-1¾)		1360-2¾ 861 (900-2¾)

WILLIAM L WHITEHURST FLD (M08)
RNAV (GPS) RWY 19