

FORT INDIANTOWN GAP, PENNSYLVANIA

COPTER RNAV (GPS) RWY 25


WAAS CH 95177 W25A	APCH CRS 250°	Rwy ldg TDZE Arprt Elev	3860 487 487
--------------------------	------------------	-------------------------------	--------------------

(USA)



MUIR AHP (FORT INDIANTOWN GAP) (KMUI)

RNP APCH - GPS	MISSED APPROACH: Climb to 1700 then climbing left turn to 3000 direct to BAARN and hold.
* When local altimeter not received, use Harrisburg Intl altimeter setting. Increase all DA by 64', vis by 1/8 miles. ** When local altimeter not received, use Harrisburg Intl altimeter setting. Increase MDA 80', vis 1/4 miles.	

ASOS 124.175	HARRISBURG APP CON/DEP CON 118.25 269.45	TOWER★ 126.2 (CTAF) 290.325	GND CON 135.675 269.525
-----------------	---	--------------------------------	----------------------------



1700	3000	BAARN	VGSI and descent angles not coincident.	RUZZL	ELEV 487	TDZE 487
↑	↖	⬤		070° → 6000 ← 250° 4000		



CATEGORY	COPTER	
LPV DA*	816-1	329 (400-1)
LNAV/VNAV DA*	1166-1 7/8	679 (700-1 7/8)
LNAV MDA**	1300-1	813 (900-1)
WITH HARRISBURG INTL ALTIMETER SETTING		
LPV DA	880-1 1/8	393 (400-1 1/8)
LNAV/VNAV DA	1230-2	743 (800-2)
LNAV MDA	1380-1 1/4	893 (900-1 1/4)

FORT INDIANTOWN GAP, PENNSYLVANIA

40°26'N - 76°34'W MUIR AHP (FORT INDIANTOWN GAP) (KMUI)

Amdt 1 23JAN25

COPTER RNAV (GPS) RWY 25

NE-4, 01 OCT 2026 to 29 OCT 2026

NE-4, 01 OCT 2026 to 29 OCT 2026