


WAAS CH 61119 W35A	APP CRS 354°	Rwy Idg TDZE Apt Elev	3501 1026 1030
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

BLACKWELL-TONKAWA MUNI (BKN)

RNP APCH. ▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Ponca City altimeter setting and increase all DA 31 feet and all MDA 40 feet and LNAV/VNAV all Cats visibility ¼ mile. Baro-VNAV and VDP NA when using Ponca City altimeter setting.	MISSED APPROACH: Climb to 2800 direct EWAIT and hold.
---	---

AWOS-3PT 120.575	KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



2800	EWAIT	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 40).			
*LNAV only		WINBI 2 NM to RW35	KIZMA 2600	IOLLA 2800	4 NM Holding Pattern
RW35		*1 NM to RW35	2600	174°	354°
1 NM		1 NM	2.8 NM	6.1 NM	GP 3.00° TCH 40
CATEGORY	A	B	C	D	
LPV DA	1276-1	250 (300-1)		NA	
LNAV/VNAV DA	1324-1	298 (300-1)		NA	
LNAV MDA	1340-1	314 (400-1)		NA	