

WAAS CH 60929 W29A	APP CRS 289°	Rwy Ldg TDZE Apt Elev	6000 308 310
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 29

SOUTH ALABAMA RGNL AT BILL BENTON FLD (79J)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Cairns AAF (Fort Rucker) altimeter setting and increase all DA 82 feet, all MDA 100 feet. Increase LPV and LNAV/VNAV visibilities ¾ mile, LNAV and Circling Cat C and D ¼ mile. Baro-VNAV and VDP NA when using Cairns AAF (Fort Rucker) altimeter setting.

MISSED APPROACH: Climb to 2500 direct ZELAS and hold.

ASOS 134.875	CAIRNS APP CON ★ 133.45 239.275	UNICOM 123.05 (CTAF) 0
------------------------	---	----------------------------------



ELEV 310 TDZE 308

MIRL Rwy 11-29 0
REIL Rwy 11 and 29

2500	ZELAS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 47).		4 NM Holding Pattern
*LNAV only WEDIP 2 NM to RW29 JAZZU 1600 ALANE 109° 289° 2000 GP 3.00° TCH 45				
1 NM 1 NM 1.9 NM 7 NM				
CATEGORY				
LPV DA	630-1 322 (400-1)			
LNAV/VNAV DA	628-1 320 (400-1)			
LNAV MDA	720-1 412 (500-1)		720-1½ 412 (500-1½)	
CIRCLING	820-1 510 (600-1)		860-1½ 550 (600-1½) 940-2 630 (700-2)	

SE-4, 01 OCT 2026 to 29 OCT 2026

SE-4, 01 OCT 2026 to 29 OCT 2026