

APP CRS
292°

Rwy Ldg
TDZE
Apt Elev

3600
1607
1607

RNP APCH - GPS.

NA

Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Baro-VNAV NA when using DVL altimeter setting. When local altimeter setting not received, use DVL altimeter setting: increase LNAV/VNAV DA to 2230 feet and all visibilities ¾ SM; increase all MDAs 140 feet and LNAV visibility Cat C ¾ SM and Circling visibility Cat C ½ SM.

MISSED APPROACH:
Climb to 3400 direct
NUTFO and hold.

AWOS-3 118.825	MINNEAPOLIS CENTER 135.25 256.7	UNICOM 122.8 (CTAF) 0
-------------------	------------------------------------	--------------------------

ELEV 1607 TDZE 1607

3400

NUTFO

IPREZ

IGIDY

RW29

3100

3300

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 27).

4 NM Holding Pattern

112° 3300

292°

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LNAV/VNAV DA	2100-1 ¾ 493 (500-1 ¾)			NA
LNAV MDA	2100-1	493 (500-1)	2100-1 ¾ 493 (500-1 ¾)	NA
CIRCLING	2120-1	513 (600-1)	2300-2 693 (700-2)	NA

HARVEY, NORTH DAKOTA

Orig-F 14MAY26

47°47'N-99°56'W

HARVEY MUNI (5H4)

RNAV (GPS) RWY 29