

D-ATIS DEP
134.025
CLNC DEL
118.75
CPDLC
DENVER DEP CON
128.25 371.95

(EPKEE7.EPKEE) 20142
EPKEE SEVEN DEPARTURE (RNAV)


AL-9077 (FAA)

DENVER INTL (DEN)
DENVER, COLORADO

TOP ALTITUDE:
FL230

TAKEOFF MINIMUMS

- Rwys 7, 26: NA-ATC.
Rwys 8, 16L: Standard with minimum climb of 400' per NM to 5934.
Rwy 16R: Standard with minimum climb of 450' per NM to 5934.
Rwys 17L/R: Standard with minimum climb of 465' per NM to 5934.
Rwy 25: Standard
Rwys 34L/R: Standard with minimum climb of 500' per NM to 5934,
Rwys 35L/R: Standard with minimum climb of 320' per NM to 5934.



NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

NOTE: Turbojets only.

NOTE: Rwy 25 RADAR required.

NOTE: Takeoff Rwys 8, 16L/R, 17L/R, 34L/R, 35L/R, RADAR required for non-GPS equipped aircraft.

NOTE: Accelerate to 250K or greater upon reaching 10000. If slower speed is required to meet crossing restrictions advise CLNC DEL prior to taxi.

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)