

WAAS CH 40125 W31A	APP CRS 315°	Rwy Ldg 5500 TDZE 814 Apt Elev 814
--	------------------------	---


RNAV (GPS) RWY 31
CANANDAIGUA (TUA)

RNP APCH-GPS.


NA For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use ROC altimeter setting and increase LPV DA to 1146 feet and all visibilities $\frac{1}{4}$ SM. Increase LNAV/VNAV DA to 1328 feet and all visibilities $\frac{1}{8}$ SM. Increase all MDAs 100 feet and LNAV visibility Cat C $\frac{3}{8}$ SM, and Circling visibility Cat C $\frac{1}{2}$ SM. Rwy 31 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV and VDP NA when using ROC altimeter setting.

MISSED APPROACH:
Climb to 1400 then
climbing left turn to
3700 direct BUCHH
and hold.

AWOS-3P 118.675	ROCHESTER APP CON 119.55 269.6	UNICOM 122.8 (CTAF) 0
---------------------------	--	--



ELEV 814		TDZE 814
----------	--	----------



MIRL Rwy 13-31 **L**
REIL Rwy 13 and 31 **L**

4 NM Holding Pattern

180°

90°

360°

1.4 NM to RW31

SHUBE 2400

315°

SSTAN

3200

GP 3.00° TCH 40

1.4

3.5 NM

6.8 NM

CATEGORY	A	B	C	D
LPV DA	1064-1	250 (300-1)		NA
RNAV/VNAV DA	1246-1¼	432 (500-1¼)		NA
RNAV MDA	1300-1	486 (500-1)	1300-1¾ 486 (500-1¾)	NA
CIRCLING	1460-1	646 (700-1)	1540-2 726 (800-2)	NA

RNAV (GPS) RWY 31