VOR/DME GEE	APP CRS	Rwy Ldg	N/A
108.2	085°	TDZE	N/A
Chan 19		Apt Elev	814

VOR-A

CANANDAIGUA (IUA)

DME or RADAR requried.

When local altimeter setting not received, use Rochester altimeter setting and increase all MDAs 100 feet and Circling visibility all Cats ¼ SM, increase WIVRI Fix Circling minimums visibility Cat C ½ SM.

MISSED APPROACH: Climb to 2000 then climbing right turn to 3500 direct GEE VOR/DME and hold.

AWOS-3P	ROCHESTER APP CON	UNICOM
118.675	119.55 269.6	122.8 (CTAF) L

NoPT for arrival on GEE VOR/DME airway radials 153 CW 018.







CATEGORY	A	B	C	D
CIRCLING	1580-1	766 (800-1)	1580-2¼ 766 (800-2¼)	NA

MIRL Rwy 13-31 L
REIL Rwys 13 and 31 L

WIVRI FIX MINIMUMS

CIRCLING	1500-1	686 (700-1)	1540-2 726 (800-2)	NA

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

NE-2, 01 OCT 2026 to 29 OCT 2026