

WAAS CH 63022 W06A	APP CRS 067°	Rwy Ldg TDZE 665 Apt Elev 665
--	------------------------	---

RNAV (GPS) RWY 6


SANDUSKY COUNTY RGNL (S24)


RNP APCH - GPS.


⚠ Baro-VNAV and VDP NA when using TOL altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use TOL altimeter setting: increase LPV DA to 1008 feet and all visibilities $\frac{3}{8}$ SM; increase LNAV/VNAV DA to 1041 feet and all visibilities $\frac{3}{8}$ SM; increase all MDA 100 feet and LNAV visibility Cat C and D $\frac{3}{8}$ SM and Circling visibility Cat C and D $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 3000 direct
OBOZE and hold.

AWOS-3P 119.575	TOLEDO APP CON 126.1 307.0	UNICOM 123.05 (CTAF) 0
---------------------------	--------------------------------------	----------------------------------



4 NM Holding Pattern		3000 ↑		OBOZE 	
					
CATEGORY	A	B	C	D	
LPV DA		915- $\frac{3}{4}$	250 (300- $\frac{3}{4}$)		
LNAV/ VNAV DA		948- $\frac{7}{8}$	283 (300- $\frac{7}{8}$)		
LNAV MDA		1040-1	375 (400-1)		
CIRCLING	1120-1 455 (500-1)	1160-1 495 (500-1)	1380-2 715 (800-2)	1380-2 $\frac{1}{4}$ 715 (800-2 $\frac{1}{4}$)	



EC-2, 01 OCT 2026 to 29 OCT 2026

EC-2, 01 OCT 2026 to 29 OCT 2026