


WAAS CH 72834 W19A	APP CRS 191°	Rwy Ldg 5001 TDZE 221 Apt Elev 221
--	------------------------	---

RNAV (GPS) RWY 19
PANOLA COUNTY (PMU)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).
▲ NA DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Oxford altimeter setting.
When local altimeter setting not received, use Oxford altimeter setting and increase LPV DA to 571, LNAV/VNAV DA to 1116 and all MDA 80 feet, increase LPV all Cats visibility $\frac{3}{8}$ mile, LNAV/VNAV all Cats visibility $\frac{1}{2}$ mile, LNAV Cat B visibility $\frac{1}{4}$ mile, LNAV Cats C, D visibility $\frac{1}{2}$ mile, and Circling Cats B, C visibility $\frac{1}{4}$ mile. Rwy 19 helicopter visibility reduction below $\frac{3}{4}$ SM NA.


MISSED APPROACH:
Climb to 1100 then climbing left turn to 2800 direct SUBOY and hold.

AWOS-3PT 118.225	MEMPHIS CENTER 128.5 279.55	UNICOM 122.8 (CTAF) 0
----------------------------	---------------------------------------	---------------------------------



ELEV 221	TDZE 221
----------	----------

MIRL Rwy 1-19 0

1100	2800	SUBOY	VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 45).			
			4 NM Holding Pattern			
*LNAV only.						
						
CATEGORY			A	B	C	D
LPV	DA	500-7/8 279 (300-7/8)				
LNAV/ VNAV	DA	1045-3 824 (900-3)				
LNAV	MDA	940-1 719 (800-2)		940-2 719 (800-2)		
CIRCLING		940-1 719 (800-1)	1000-1 779 (800-1)	1000-2 1/4 779 (800-2 1/4)	1120-3 899 (900-3)	

SC-4, 01 OCT 2026 to 29 OCT 2026

SC-4, 01 OCT 2026 to 29 OCT 2026