

APP CRS

237°

Rwy Ldg

3934

TDZE

365

Apt Elev

365

RNAV (GPS) RWY 23

BEAVER (WBQ)(PAWB)

RNP APCH-GPS.

▼

NA

Rwy 23 helicopter visibility reduction below ¾ SM NA.

Use Fort Yukon altimeter setting.

MISSED APPROACH: Climb to 3000 direct ZUSPA and hold.

FYU/PFYU AWOS-3P 125.8	FAIRBANKS RADIO 122.05 122.15	CTAF 122.9 0
---------------------------	----------------------------------	-----------------

The main chart illustrates the RNAV (GPS) RWY 23 approach. Key features include:

- ZUSPA:** Initial approach fix, 4 NM from RWY 23, 056° to 236°.
- CEKNA (FAF):** Final approach fix, 2000 ft, 237° to RWY 23.
- WADUB:** Intermediate approach fix, 3000 ft, 057° to CEKNA, 16 NM to WADUB, 30 NM to WADUB.
- DUTKE:** Intermediate approach fix, 3000 ft, 057° to CEKNA, 30 NM to DUTKE (NoPT), 12 NM to DUTKE.
- KULBE:** Intermediate approach fix, 3000 ft, 057° to CEKNA, 30 NM to KULBE, 8 NM to KULBE.
- Holding Patterns:** 4 NM holding patterns at 10000 ft and 3000 ft for ZUSPA, CEKNA, and DUTKE.

ELEV 365

TDZE 365

3000

ZUSPA

3934 X 75

23

3000

CEKNA

2000

DUTKE

4 NM Holding Pattern

3000

CEKNA

2000

DUTKE

4 NM Holding Pattern

MIRL Rwy 5-23 0

CATEGORY	A	B	C	D
LNAV MDA	940-1	575 (600-1)	940-1½ 575 (600-1½)	NA
CIRCLING	940-1	575 (600-1)	940-1½ 575 (600-1½)	NA

BEAVER, ALASKA

Orig-A 02DEC21

66°22'N-147°24'W

BEAVER (WBQ)(PAWB)

RNAV (GPS) RWY 23