LOC/DME I-ONA	APP CRS	Rwy Ldg 5199
109.35	300°	TDZE 656
Chan 30 (Y)		Apt Elev 656

ILS Y or LOC Y RWY 30

WINONA MUNI/MAX CONRAD FLD (ONA)

DME required.


VDP NA with La Crosse altimeter setting. When local altimeter setting not received, use La Crosse altimeter setting and increase S-ILS 30 DA to 1127 and all visibilities ⅛ mile, increase all MDA 60 feet, and visibility S-LOC 30 Cat C/D ⅛ mile, and Circling Cat B ¼ mile. For inop ALS, increase S-ILS 30 all Cats visibility to 1⅜ mile, increase S-LOC 30 Cats C/D visibility to 1⅝ mile. For inop ALS when using La Crosse altimeter setting, increase S-ILS 30 all Cats visibility to 1⅝ mile, increase S-LOC 30 Cats C/D visibility to 1¾ mile.

NA -29°C


MALSR


MISSED APPROACH: Climb to 1800 then climbing left turn to 3000 on RST VOR/DME R-056 to VUZID INT and hold.

AWOS-3	MINNEAPOLIS CENTER	UNICOM
118.075	128.6 363.0	122.8 (CTAF) L



ELEV 656	D	TDZE 656





CATEGORY	A	B	C	D
S-ILS 30	1074-1⅛ 418 (500-1⅛)			
S-LOC 30	1220-½ 564 (600-½)		1220-1¼ 564 (600-1¼)	
CIRCLING	1560-1¼ 904 (1000-1¼)	1600-1¼ 944 (1000-1¼)	1780-3 1124 (1200-3)	1980-3 1324 (1400-3)

REIL Rwy 12 L
MIRL Rwy 12-30 L

NC-1, 29 OCT 2026 to 26 NOV 2026
NC-1, 29 OCT 2026 to 26 NOV 2026