ILS or LOC RWY 26L

GEORGE BUSH INTCNTL/HOUSTON (IAH)

LOC/DME I-JYV	APP CRS	Rwy Ldg	9402
109.7	267°	TDZE	95
Chan 34		Apt Elev	96


DME required. From BOZZZ, GARRR: RNAV 1-GPS required.


Simultaneous approach authorized with Rwy 26R and Rwy 27. For inop ALS, increase S-ILS 26L Cat E visibility to RVR 4000, S-LOC 26L Cat C/D/E visibility to RVR 5000.


ALSF-2

MISSED APPROACH: Climb to 3000 then left turn heading 240° and IAH VORTAC R-270 to LUCEP INT/IAH 22.9 DME and hold.

D-ATIS	HOUSTON APP CON	HOUSTON TOWER	GND CON
124.05	120.05 379.1 E 124.35 316.15 W	125.35 290.2	118.575







TDZ/CL Rwys 8R, 8L, 15R, 26R, 26L, 27 and 33L
HIRL all Rwys

CATEGORY	A	B	C	D	E
S-ILS 26L	295/18 200 (200-½)				
S-LOC 26L	460/24 365 (400-½)		460/35 365 (400-⅝)		

FAF to MAP 5.8 NM

Knots	60	90	120	150	180
Min:Sec	5:48	3:52	2:54	2:19	1:56

SC-5, 29 OCT 2026 to 26 NOV 2026
SC-5, 29 OCT 2026 to 26 NOV 2026