# BOTCH TWO DEPARTURE (RNAV)

(BOTCH2.BOTCH) 14MAY26

DALLAS, TEXAS

DALLAS LOVE FLD (DAL)

**TOP ALTITUDE: ASSIGNED BY ATC**

RNAV 1 - DME/DME/IRU or GPS required.

RADAR required.

LONE STAR DEP CON
124.3 282.275 (31L/R Props)
125.2 343.65 (13L/R Props)
D-ATIS
120.15
CLNC DEL
127.9
CPDLC
GND CON
121.75 348.6
LOVE TOWER
123.7 239.3

NOTE: ALIAN Transition: ATC assigned only.
NOTE: Props only.

HUDAD
9000 *3000 291° (66)
MUTEE
9000 *3600 291° (27)
PGLET
9000 *2600 308° (16)
HULZE
9000 *3100 285° (37)
HRPER
9000 *3000 288° (69)
DBLSS
9000 *2800 288° (27)
TYGGR
9000 *2500 287° (13)
BRHMA
9000 *4000 282° (75)
KATZZ
9000 *3500 282° (71)
RUFFS
9000 *2800 283° (26)
9000 *2500 256° (12)
ROOOO
ALIAN
9000 *3200 268° (51)
FUMED
9000 *3100 268° (25)
9000 *2500 232° (15)
LYNDE
9000 *3300 262° (56)
9000 *3100 262° (25)
RBBIT
CIKAN
9000 *4100 263° (50)
WSTEX
9000 *3700 251° (33)
DOSXX

1300
258°
259°
313°
313°
133°
133°
262°
261°
987
BOTCH
13000
270° (13) DEMII
5000

N

MSA DAL 25 NM
3600

TAKEOFF MINIMUMS
Rwys 31L/R: Standard.
Rwys 13L: Standard with minimum climb of 290'/NM to 1700.
Rwys 13R: Standard with minimum climb of 315'/NM to 1700.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(BOTCH2.BOTCH) 26134
BOTCH TWO DEPARTURE (RNAV)
DALLAS LOVE FLD (DAL)
DALLAS, TEXAS

AL-106 (FAA)