LOVE SEVEN DEPARTURE (LOVE7.TTT) 26DEC24

DALLAS, TEXAS
DALLAS LOVE FLD (DAL)

TOP ALTITUDE: 5000

DME and RADAR required.

LONE STAR DEP CON
118.55 290.35
D-ATIS
120.15
CLNC DEL 127.9
CPDLC
GND CON
121.75 348.6
LOVE TOWER
123.7 239.3

TAKEOFF MINIMUMS
Rwys 13L, 31L/R: NA - Noise abatement.
Rwy 13R: Standard with minimum climb of 320'/NM to 1700.

PANHANDLE
116.6 PNH
Chan 113

TEXICO
112.2 TXO
Chan 59

CHILDRESS
117.0 CDS
Chan 117

WICHITA FALLS
112.7 SPS
Chan 74

RANGER
115.7 FUZ
Chan 104

COWBOY
116.2 CVE
Chan 109

CORONA
115.5 CNX
Chan 102

LUBBOCK
109.2 LBB
Chan 29

ABILENE
113.7 ABI
Chan 84

MILLSAP
117.7 MQP
Chan 124

MAVERICK
113.1 TTT
Chan 78

LOCALIZER 111.1
I-DPX
Chan 48

R-117 FL180 *4900 297° (87) V114

R-125 FL180 *5500 305° (66) V62

FL180 *8300 R-092 272° (192)

R-127 FL180 *3100 307° (61)

R-233

SCABI 129 14000 *3000 285° (92)

FERRA 4000 *2400 285° (37)

R-104 FL180 *4600 284° (127)

FUZ R-261

KIRST FL180 *3500 264° (94) CEOLA 4000 *2500 264° (35)

129 4000 *3500 253° (96) V66 R-022 R-071 R-081

4000 *2800 261° (13) PODDE

3500 *2800 250° (36)

I-DPX 0.7 163° CVE R-139

NOTE: This departure procedure is to be used only upon assignment by Love Tower normally between 2100-0600 LCL time.

NOTE: PODDE TRANSITION: ATC assigned.

N

MSA TTT 25 NM
2700
090° 270°
3600

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

LOVE SEVEN DEPARTURE (LOVE7.TTT) 26246
DALLAS LOVE FLD (DAL)
DALLAS, TEXAS

AL-106 (FAA)