BOTCH TWO DEPARTURE (RNAV)

(BOTCH2.BOTCH) 14MAY26

FORT WORTH MEACHAM INTL (FTW)

FORT WORTH, TEXAS

TOP ALTITUDE: ASSIGNED BY ATC

RNAV 1 - DME/DME/IRU or GPS required.

RADAR required.

LONE STAR DEP CON
118.1 306.95 (N)
135.975 379.9 (S)
ATIS
120.7
CLNC DEL
124.65
GND CON
121.9
MEACHAM TOWER
118.3 257.8

MSA FTW 25 NM
3600

HUDAD
HULZE
HRPER
MUTEE
PGLET
BRHMA
DBLSS
TYGGR
KATZZ
RUFFS
ROOOO
ALIAN
FUMED
LYNDE
WSTEX
CIKAN
RBBIT
DOSSX
BOTCH
13000
DEMII
5000
1210
1600

9000 *3000 291° (66)
9000 *3100 285° (37)
9000 *3600 291° (27)
9000 *3000 288° (69)
9000 *2800 288° (27)
9000 *2600 308° (16)
9000 *4000 282° (75)
9000 *2500 287° (13)
9000 *3500 282° (71)
9000 *2800 283° (26)
9000 *2500 256° (12)
9000 *3200 268° (51)
9000 *3100 268° (25)
9000 *2500 232° (15)
9000 *4100 263° (50)
9000 *3300 262° (56)
9000 *3100 262° (25)
9000 *3700 251° (33)
270° (13)

091°
094°
344°
344°
164°
164°
084°
086°

N

NOTE: ALIAN Transition: ATC assigned only.

TAKEOFF MINIMUMS

Rwy 17: Standard.

Rwy 16: Standard with minimum climb of 204'/NM to 1400, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1400' prior to DER.

Rwy 34: 300-1⅞ or standard with minimum climb of 225'/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 2000' prior to DER.

Rwy 35: 300-1¼ or standard with minimum climb of 210'/NM to 900, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1300' prior to DER.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

(BOTCH2.BOTCH) 26134

BOTCH TWO DEPARTURE (RNAV)

AL-159 (FAA)

FORT WORTH MEACHAM INTL (FTW)

FORT WORTH, TEXAS