DALLAS FOUR DEPARTURE

(DALL4.TTT) 27NOV25

FORT WORTH MEACHAM INTL (FTTW)

FORT WORTH, TEXAS

LONE STAR DEP CON
118.1 306.95 (NORTH)
135.975 379.9 (SOUTH)
ATIS
120.7
CLNC DEL
124.65
GND CON
121.9
MEACHAM TOWER
118.3 257.8

RADAR and DME required.

NOTE: BELCHER Transition: For aircraft inbound to the JAN, MLU, and SHV terminal areas only.

NOTE: SOLDO Transition: ATC assigned.

TOP ALTITUDE: ASSIGNED BY ATC

LITTLE ROCK
115.1 LIT
Chan 98

TEXARKANA
116.3 TXK
Chan 110

BONHAM
114.6 BYP
Chan 93

MAVERICK
113.1 TTT
Chan 78

GREGG COUNTY
112.9 GGG
Chan 76

BELCHER
117.4 EIC
Chan 121

ORTRO

COBUG

NOBLY

TRISS

SHERO

SOLDO

CLARE

POTEN

TEKBE

SHRLY

18300 *2600 057° (122) R-237

FL230 *2000 064° (75) 151

R-320

5000 *2300 064° (38) 76

R-184

7500 *2100 064° (79)

R-244

R-187

(38) 5000 *2100 064°

2800 *2300 074° (36)

R-182

R-181

R-180

7500 *2100 074° (39) 76

3000 *2300 084° (36)

5000 *2400 094° (36)

9000 *2100 094° (34) 71

9000 *2100 079° (44) 94

079° 5300 *1900 (25)

R-346

50

079° 2400 (25)

R-259

164° 1600

166° 1600

MSA TTT 25 NM
2700
090° 270°
3600

TAKEOFF MINIMUMS

Rwys 16, 17: Standard.

Rwy 34: 300-1⅞ or standard with minimum climb of 225′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 2000′ prior to DER.

Rwy 35: 300-1¼ or standard with minimum climb of 210′/NM to 900, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 1300′ prior to DER.

N

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(DALL4.TTT) 25331

DALLAS FOUR DEPARTURE

AL-159 (FAA)

FORT WORTH MEACHAM INTL (FTTW)

FORT WORTH, TEXAS