KUSSO THREE DEPARTURE (RNAV)

(KUSSO3.KUSSO) 14MAY26

FORT WORTH MEACHAM INTL (FTW)

FORT WORTH, TEXAS

LONE STAR DEP CON
118.1 306.95 (N)
135.975 379.9 (S)
ATIS
120.7
CLNC DEL
124.65
GND CON
121.9
MEACHAM TOWER
118.3 257.8

RNAV 1 - DME/DME/IRU or GPS required.

RADAR required.


TOP ALTITUDE: ASSIGNED BY ATC


TAKEOFF MINIMUMS


Rwys 16, 17: Standard.

Rwy 34: 300-2 or standard with minimum climb of 225′ per NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′ per NM climb gradient, takeoff must occur no later than 2000′ prior to DER.

Rwy 35: 300-1¼ or standard with minimum climb of 210′ per NM to 900, or alternatively, with standard takeoff minimums and a normal 200′ per NM climb gradient, takeoff must occur no later than 1300′ prior to DER.







NOTE: BDDAY Transition: ATC assigned only.

NOTE: MRSSH Transition: For aircraft inbound to Shreveport, Jackson and Monroe terminal area airports only.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(KUSSO3.KUSSO) 26134

KUSSO THREE DEPARTURE (RNAV)

AL-159 (FAA)

FORT WORTH MEACHAM INTL (FTW)

FORT WORTH, TEXAS