LOC/DME I-GQR	APP CRS	Rwy Ldg	4270
111.75	035°	TDZE	744
Chan 54 (Y)		Apt Elev	757

ILS or LOC RWY 4


KANSAS CITY DOWNTOWN/WHEELER FLD (MKC)


DME or RADAR required for procedure entry. DME or RADAR required for LOC only.

Circling NA east of Rwy 1-19. Autopilot coupled approach NA below 1013. Circling NA to Rwy 22. Circling NA for Cat D to Rwy 4. Rwy 4 helicopter visibility reduction below RVR 4000 NA.


MISSED APPROACH: Climb to 3100 then right turn heading 100° and on ANX VORTAC R-295 to ANX VORTAC and hold.

ATIS	KANSAS CITY APP CON	DOWNTOWN TOWER	GND CON
120.75	118.4 307.35	133.3 233.7	121.9





CATEGORY	A	B	C	D
S-ILS 4	1001/40 257 (300-¾)			NA
S-LOC 4	1560/55 816 (900-1)	1560-1¼ 816 (900-1¼)	1560-2½ 816 (900-2½)	NA
CIRCLING	1560-1 803 (900-1)	1560-1¼ 803 (900-1¼)	1560-2½ 803 (900-2½)	
WIKTU FIX MINIMUMS				
S-LOC 4	1240/55 496 (500-1)		1240-1⅜ 496 (500-1⅜)	NA
CIRCLING	1380-1 623 (700-1)	1400-1 643 (700-1)	1460-2 703 (800-2)	1540-2½ 783 (800-2½)



FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

NC-3, 26 NOV 2026 to 24 DEC 2026
NC-3, 26 NOV 2026 to 24 DEC 2026