RNAV (RNP) Y RWY 17L

RENO/TAHOE INTL (RNO)


APP CRS	Rwy Ldg	9000
167°	TDZE	4415
	Apt Elev	4415

RNP AR APCH - GPS, RF. Authorization required.
From HOMES: Min RNP 0.50.

T -13°C For uncompensated Baro-VNAV systems, procedure NA below -10°C or above 54°C.


MISSED APPROACH: Climb to 13000 on track 167° to ZIDGO and on track 184° to USINE and on track 127° to YARKU and hold, continue climb-in-hold to 13000.
* Missed approach requires minimum climb of 266 feet per NM to 7200.
# Missed approach requires minimum climb of 212 feet per NM to 7160.

D-ATIS	NORCAL APP CON	RENO TOWER	GND CON
135.8 363.0	119.2 279.55 126.3 353.9	118.7 257.8	121.9 348.6



13000 tr 167°	ZIDGO	tr 184°	USINE	tr 127°	YARKU


See planview for multiple IF locations.



CATEGORY	A	B	C	D
RNP 0.12 DA*		4754-1	339 (400-1)	
RNP 0.17 DA#		5019-1¾	604 (700-1¾)	
RNP 0.30 DA		5115-2	700 (700-2)	

AUTHORIZATION REQUIRED

ELEV 4415 D TDZE 4415



MIRL Rwy 8-26
REIL Rwys 8, 17L, 26, and 35R
HIRL Rwys 17R-35L and 17L-35R

SW-4, 26 NOV 2026 to 24 DEC 2026
SW-4, 26 NOV 2026 to 24 DEC 2026