LOC/DME I-SBA	APP CRS	Rwy Ldg	6052
110.3	075°	TDZE	13
Chan 40		Apt Elev	14

ILS or LOC RWY 7
SANTA BARBARA MUNI (SBA)


VDP NA when using OXR altimeter setting. Circling Rwy 15L/R and 33L/R NA at night. When local altimeter setting not received, use OXR altimeter setting: increase DA to 296 feet; increase all MDAs 100 feet and S-LOC 7 visibility Cats C and D to 1⅜ SM, Circling Cat A visibility to 1¼ SM and Circling visibility Cat C to 2¾ SM. For inop ALS, when using OXR altimeter setting, increase S-ILS 7 all Cats visibility to RVR 4500 and S-LOC 7 Cats C and D visibility to 1⅞ SM. Circling NA for Cats C and D north of Rwy 7-25.

*RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using OXR altimeter setting).


MALSR


MISSED APPROACH: Climb to 700 then climbing right turn to 4000 on RZS VORTAC R-185 to GOLET INT/RZS 14.4 DME and hold, continue climb-in-hold to 4000.

ATIS	SANTA BARBARA APP CON*	SANTA BARBARA TOWER*	GND CON	UNICOM
132.65	120.55 319.15 (151°-329°) 125.4 291.1 (330°-150°)	119.7 (CTAF) L 254.35	121.7	122.95



ELEV	14	D	TDZE	13





CATEGORY	A	B	C	D
S-ILS 7*	213/24 200 (200-½)			
S-LOC 7	560/24 547 (600-½)		560/60 547 (600-1¼)	
CIRCLING	800-1 786 (800-1)	840-1¼ 826 (900-1¼)	840-2½ 826 (900-2½)	1000-3 986 (1000-3)

HIRL Rwy 7-25 L
MIRL Rwy 15R-33L L
REIL Rwys 15R and 25 L

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

SW-3, 26 NOV 2026 to 24 DEC 2026
SW-3, 26 NOV 2026 to 24 DEC 2026