FAIRFIELD, CALIFORNIA

RNAV (GPS) RWY 03R

WAAS	APCH CRS	Rwy ldg	10,995
CH 98057	035°	TDZE	59
W03B		Arpt Elev	63

(USAF) TRAVIS AFB (KSUU)

RNP APCH

▼ * Circling NA NW of RWY 3L-21R.

MISSED APPROACH: Climb to 4500 direct FOLNO, track 308° to SEATO and hold, continue climb-in-hold to 4500.

ATIS	APP CON	TOWER	GND CON
135.55 292.125	119.9 322.325 (S) 126.6 281.45 (N)	120.75 254.4	121.8 289.4

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

5 NM 163° 343° SEATO

RADAR required when holding above 6000.

308° (10.9) FOLNO

199

RW03R

WUSMO

(FAF) LUDEC 035° 253 427

HEIDY 2500 1900 (3) 306

1159 2500 036° (6.5)

(IF/IAF) HABAL 3000

MSA RW03R 25 NM 5100

EMERG SAFE ALT 100 NM 12,600

4500 FOLNO tr 308° SEATO

ELEV 63 TDZE 59

HABAL 3000 036° HEIDY 2500 LUDEC 035° WUSMO 1.3 NM to RW03R RW03R

1900 900

GP 3.00° TCH 50

VGSI and RNAV glidepath not coincident (VGSI angle 2.50°/TCH 69)

3.1 NM 2.5 NM

BCN TWR 209 10,995 x 150 3500 x 90 212° 032° 035° 11,001 x 150 ASSAULT STRIP

CATEGORY	A	B	C	D	E
LPV DA	259/40		200	(200-¾)	
LNAV/VNAV DA	340/45 281 (300-⅞)	351/45 292 (300-⅞)	359/45 300 (300-⅞)	370/45 311 (400-⅞)	
LNAV MDA	460/55 401 (400-1)		460/60	401 (400-1⅛)	
CIRCLING*	560-1 497 (500-1)	660-1 597 (600-1)	1100-3 1037 (1100-3)	1200-3 1137 (1200-3)	

HIRL Rwys 3L-21R and 3R-21L
TDZL/RCLS Rwys 3R and 21L

FAIRFIELD, CALIFORNIA 38°16'N - 121°55'W TRAVIS AFB (KSUU)

Orig 27JAN22

RNAV (GPS) RWY 03R

SW-2, 26 NOV 2026 to 24 DEC 2026