WAAS	APP CRS	Rwy Ldg	5500
CH 86607	353°	TDZE	1946
W35A		Apt Elev	1953


RNAV (GPS) RWY 35

PRATT RGNL (PTT)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Great Bend altimeter setting: Increase LPV DA to 2295 feet and all visibilities ¼ SM; Increase LNAV/VNAV DA to 2421 feet and all visibilities ½ SM; Increase all MDAs 100 feet and visibility Cat C ¼ SM. Baro-VNAV and VDP NA when using Great Bend altimeter setting.

MISSED APPROACH: Climb to 4300 direct ORLIE and hold.


AWOS-3PT	KANSAS CITY CENTER	UNICOM
118.725	118.8 322.425	122.8 (CTAF) L




ELEV 1953	TDZE 1946

REIL Rwys 17 and 35 L

MIRL Rwy 17-35 L





CATEGORY	A	B	C	D
LPV DA	2196-1 250 (300-1)			NA
LNAV/VNAV DA	2322-1¼ 376 (400-1¼)			NA
LNAV MDA	2320-1 374 (400-1)			NA
CIRCLING	2380-1 427 (500-1)	2420-1 467 (500-1)	2580-1¾ 627 (700-1¾)	NA

NC-2, 26 NOV 2026 to 24 DEC 2026
NC-2, 26 NOV 2026 to 24 DEC 2026