WAAS CH 90132 W06A	APP CRS 060°	Rwy Ldg 5188 TDZE 586 Apt Elev 592

RNAV (GPS) RWY 6


NIAGARA FALLS INTL (IAG)


RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.
Rwy 6 helicopter visibility reduction below 1 SM NA.
Rwy 6 Straight-in and Circling minimums NA at night.


MISSED APPROACH: Climb to 3600 direct ZUPUV and hold, continue climb-in-hold to 3600.

ATIS	BUFFALO APP CON	NIAGARA TOWER ★	GND CON	UNICOM
120.8 269.4	126.5 317.6	118.5 (CTAF) L 349.0	125.3 275.8	122.95





CATEGORY	A	B	C	D
LPV DA		864-1	278 (300-1)	
LNAV/VNAV DA		849-1	263 (300-1)	
LNAV MDA	1000-1 414 (500-1)		1000-1⅛ 414 (500-1⅛)	
CIRCLING	1100-1 508 (600-1)		1280-2 688 (700-2)	1280-2¼ 688 (700-2¼)



REIL Rwys 6 and 24 L
TDZL/RCLS Rwy 28 L
RCLS Rwy 10 L
HIRL Rwy 10-28 L
MIRL Rwys 6-24 L

NE-2, 26 NOV 2026 to 24 DEC 2026
NE-2, 26 NOV 2026 to 24 DEC 2026