ILS or LOC RWY 1

ALPENA COUNTY RGNL (APN)

LOC I-APN	APP CRS	Rwy Ldg	9001
109.7	007°	TDZE	685
		Apt Elev	690

ADF required.

For inop ALS, increase S-LOC 1 Cat C/D visibility to 1⅝ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 2800 direct AP LOM and hold.

ATIS	ALPENA APP CON ★	ALPENA TOWER ★	GND CON	UNICOM
120.675 327.05	128.425 379.3	121.35 (CTAF) L 318.1	121.9 275.8	122.95

ALTERNATE MISSED APCH FIX

R-355-175°-355°

ALPENA APN 116.5 Chan 112

LOCALIZER 109.7 I-APN

ALPENA 116.5 APN Chan 112

799±

2800 to LOM 188° (7.3)

HOMSU APN 2.8

LOM/IAF FELPS 206 AP APN 7.3

187°

007°

(9)

2800

(IF) YARLU APN 13.3

2800 to YARLU 090° (3.9) and 007° (7.3)

142°

322°

(IAF) AILES APN 17

187°

MSA APN 25 NM

180°

3500

090°


2700


ELEV 690 D TDZE 685

HIRL Rwy 1-19 L

MIRL Rwy 7-25 L

REIL Rwys 7, 19 and 25 L





CATEGORY	A	B	C	D
S-ILS 1	885-½ 200 (200-½)			
S-LOC 1	1260-½ 575 (600-½)		1260-1¼ 575 (600-1¼)	
HOMSU FIX MINIMUMS				
S-LOC 1	1140-½ 455 (500-½)		1140-⅞ 455 (500-⅞)	

FAF to MAP 6.3 NM

Knots	60	90	120	150	180
Min:Sec	6:18	4:12	3:09	2:31	2:06

EC-1, 26 NOV 2026 to 24 DEC 2026
EC-1, 26 NOV 2026 to 24 DEC 2026