TOP ALTITUDE:
ASSIGNED BY ATC
RADAR and DME required.
LONE STAR DEP CON
125.2 343.65
ATIS
126.35
CLNC DEL
118.625
GND CON
119.475
EXECUTIVE TOWER ★
127.25 (CTAF)
TAKEOFF MINIMUMS
Rwys 13, 31, 35: Standard.
Rwy 17: 400-2¾ or standard with
minimum climb of 220'/NM to 1200.
MAVERICK
113.1 TTT
Chan 78
WICHITA FALLS
112.7 SPS
Chan 74
LUBBOCK
109.2 LBB
Chan 29
ABILENE
113.7 ABI
Chan 84
MILLSAP
117.7 MQP
Chan 124
KARYN
MUZZO
FERRA
PODDE
V568
V62
V66
65
R-148
R-114
R-071
R-081
R-330
3100
328°
(25)
4000
*3000
330°
(22)
6000
*4800
296°
(127)
4000
*3000
285°
(27)
2700
*2400
285°
(37)
3500
*2800
250°
(36)
3000
261°
(13)
3700
253°
(96)
1400
1800
354°
129°
309°
174°
1500
2600
N
NOTE: LUBBOCK Transition: For all aircraft overflying the MQP VORTAC westbound or direct.
NOTE: MILLSAP Transition: For all aircraft overflying the MQP VORTAC westbound or direct.
NOTE: PODDE Transition: ATC assigned.
NOTE: WICHITA FALLS Transition: For all aircraft landing within the Wichita Falls terminal area or overflying the SPS VORTAC.
NOTE: For all aircraft requesting 17000 and below.
NOTE: Chart not to scale.
NMSA TTT 25 NM
2700
3600
090°
270°
(CONTINUED ON FOLLOWING PAGE)