LOC I-SOU	APP CRS	Rwy Ldg	9072
110.1	013°	TDZE	1180
		Apt Elev	1205

ILS or LOC RWY 1

MARQUETTE SAWYER RGNL (SAW)

DME required for LOC only.

NA Autopilot coupled approach NA below 1360 MSL.

MALSR

MISSED APPROACH: Climb to 1700 then climbing right turn to 3000 on heading 138° and on SAW VOR/DME R-095 to YEXJO INT and hold, continue climb-in-hold to 3000.

AWOS-3PT	MINNEAPOLIS CENTER	SAWYER TOWER ★	GND CON	UNICOM
118.375	119.1 290.2	119.975 (CTAF) L	121.65	122.7

LOCALIZER 110.1
I-SOU

SAWYER
117.1 SAW
Chan 118

R-095 095° 275°

YEXJO INT

3500 to EVYIP
193° (17.5)

1289±

GAMGE
SAW 3.9

FOLUK
SAW 5.9

Procedure NA for arrivals on SAW VOR/DME airway radials 165 CW 227.

R-349

113.55 ESC
Chan 82(Y)

MSA SAW 25 NM
3700
3100
250°
350°

2700

013° (17.5)

R-324

(IF/IAF)
EVYIP INT
SAW 17.5

HOLD 5000 3500

IAF
ESCANABA
113.55 ESC
Chan 82(Y)

013° 1 min 193°

193°


3500 NoPT
324° (26)

Procedure NA for arrivals on ESC VOR/DME airway radials 278 CW 341.

ELEV 1205 D TDZ 1180

HIRL Rwy 1-19 L

REIL Rwy 19 L



One Minute Holding Pattern

EVYIP INT
SAW 17.5

FOLUK
SAW 5.9

1700	3000	SAW R-095	YEXJO INT
	hdg 138°		

5000 3500 193° 013°

013°

2700

GAMGE
SAW 3.9

SAW 2.4

SAW 1.3

GS 3.00°
TCH 50

2700 2040

11.5 NM 2.1 NM 1.5 NM 1.1 NM

CATEGORY	A	B	C	D
S-ILS 1	1380-½ 200 (200-½)			
S-LOC 1	1580-½ 400 (400-½)		1580-⅝ 400 (400-⅝)	
CIRCLING	1680-1 475 (500-1)		1820-1¾ 615 (700-1¾)	1820-2 615 (700-2)

EC-1, 26 NOV 2026 to 24 DEC 2026
EC-1, 26 NOV 2026 to 24 DEC 2026