RNAV (GPS) RWY 35

EASTERWOOD FLD (CLL)

WAAS CH 63122 W35A	APP CRS 346°	Rwy Ldg 6932 TDZE 311 Apt Elev 321


RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C. For inop ALS, increase LPV Cat E visibility to ¾ SM, increase LNAV/VNAV all Cats visibility to ⅞ SM, increase LNAV Cat E visibility to 1⅜ SM.


MALSR


MISSED APPROACH: Climb to 2100 direct ZAKBU and hold.

ATIS	HOUSTON APP CON	EASTERWOOD TOWER ★	GND CON	UNICOM
126.85	134.3 360.85	118.5 (CTAF) L 284.7	128.7 284.7	122.95



ELEV 321 D TDZE 311





CATEGORY	A	B	C	D	E
LPV DA	511-½ 200 (200-½)				
LNAV/VNAV DA	619-½ 308 (300-½)				
LNAV MDA	760-½ 449 (500-½)		760-⅞ 449 (500-⅞)		
CIRCLING	860-1 539 (600-1)	880-1 559 (600-1)	1000-2 679 (700-2)	1180-2¾ 859 (900-2¾)	1180-3 859 (900-3)

SC-5, 26 NOV 2026 to 24 DEC 2026
SC-5, 26 NOV 2026 to 24 DEC 2026