ILS or LOC RWY 10

CAPE GIRARDEAU RGNL (CGI)

LOC/DME I-CGI	APP CRS	Rwy Ldg	6500
109.5	108°	TDZE	337
Chan 32		Apt Elev	342


ADF required.


For inop ALS, increase S-LOC 10 Cat C/D visibility to 1⅞ SM.

MALSR


MISSED APPROACH: Climb to 1500 then climbing left turn to 2400 direct DUTCH LOM/I-CGI 7.2 DME and hold.

ASOS	MEMPHIS CENTER	CAPE GIRARDEAU TOWER★	GND CON	UNICOM
120.55	133.65 292.15	125.525 (CTAF) L	124.7	122.95





ELEV 342 D TDZE 337



CATEGORY	A	B	C	D
S-ILS 10	537-½ 200 (200-½)			
S-LOC 10	1000-½ 663 (700-½)		1000-1½ 663 (700-1½)	
CIRCLING	1000-1 658 (700-1)		1000-1⅞ 658 (700-1⅞)	1080-2¼ 738 (800-2¼)
ZAXOD FIX MINIMUMS				
S-LOC 10	660-½ 323 (400-½)			
CIRCLING	880-1 538 (600-1)	960-1 618 (700-1)	1000-1¾ 658 (700-1¾)	1080-2¼ 738 (800-2¼)

MIRL Rwy 2-20 L
HIRL Rwy 10-28 L

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58

NC-3, 26 NOV 2026 to 24 DEC 2026
NC-3, 26 NOV 2026 to 24 DEC 2026