LOS ALAMITOS, CALIFORNIA

VOR or TACAN RWY 22L

VORTAC SLI 115.7 Chan 104	APCH CRS 214°	Rwy Idg 8001 / TDZE 36 / Arpt Elev 36

[USA]

LOS ALAMITOS AAF (JOINT FORCES TRAINING BASE JFTB) (KSLI)

DME required

▼ * When ALS inop, increase CAT CD vis to 1⅜ miles.
** Circling not authorized N of Rwy 4L-22R. Circling to Rwy 4R not authorized at night.

SALSF (A2)

MISSED APPROACH: Climb to 1800, then climbing left turn to 3100 via SLI VORTAC R-058 to AHEIM INT and hold, continue climb-in-hold.

ATIS	SOCAL APP CON	TOWER	GND CON
118.875 379.975	125.35 316.125	123.85 251.15	126.95 257.95

When local altimeter setting not received, use John Wayne/Orange County altimeter setting.

POMONA 110.4 POM Chan 41

Procedure NA for arrivals at PRADO via V16-370 Eastbound.

PARADISE 112.2 PDZ Chan 59

3000 NoPT 256° R-164

(IF) ACELL SLI 12.9 PDZ 16.5

R-034 R-256 259° 079°

Max entry alt 6000 (IAF) KRUST SLI 6

REMPS SLI 10 2700 NoPT (2.9)

FULLERTON MUNI 755 1700 NoPT 214° (4)

(IAF) PRADO

351 AHEIM SLI 7.5 R-058

3100 034° (6) LETVE SLI 2.7 201

238° 200K 058° R-187

OYAVE SLI 1.7 255

HOLD 6000 3100

MSA SLI 25 NM 140° 7700 230° 6900 320° 2800 050° 4400

2000 4000

SEAL BEACH 115.7 SLI Chan 104

ELEV	36	TDZE	36

1800 | 3100 SLI R-058 | AHEIM SLI 7.5

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 75).

KRUST SLI 6 6000 3100 034°

Remain within 10 NM

LETVE SLI 2.7 OYAVE SLI 1.7 SLI VORTAC 3.28° TCH 55

REMPS SLI 10 214° 3100 2700 1700 640

0.6 ← 1 NM → 3.3 NM

TWR 22R 22L 5902 x 150 8001 x 200 4L 4R 214°

CATEGORY	A	B	C	D
S-22L*	500-1 464 (500-1)		500-1⅛ 464 (500-1⅛)	
CIRCLING**	500-1 464 (500-1)		600-1½ 564 (600-1½)	600-2 564 (600-2)
KSNA-SNA (JOHN WAYNE/ORANGE COUNTY) ALTIMETER SETTING MINIMUMS				
S-22L	540-1 504 (600-1)		540-1⅜ 504 (600-1⅜)	
CIRCLING**	540-1 504 (600-1)		640-1¾ 604 (700-1¾)	640-2 604 (700-2)

HIRL Rwy 4R-22L
MIRL Rwy 4L-22R
REIL Rwy 22L

SW-3, 26 NOV 2026 to 24 DEC 2026