RNAV (GPS) RWY 2

NEWPORT NEWS/WILLIAMSBURG INTL (PHF)


WAAS	APP CRS	Rwy Ldg	6526
CH 61020	022°	TDZE	38
W02A		Apt Elev	42


RNP APCH - GPS.


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Baro-VNAV and VDP NA when using ORF altimeter setting. When local altimeter setting not received, use ORF altimeter setting and increase LPV DA to 289 feet; increase LNAV/VNAV DA to 524 feet and all visibilities ⅛ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ⅛ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 2000 direct PANLE and hold.

ATIS	NORFOLK APP CON	NEWPORT NEWS TOWER ★	GND CON	UNICOM
128.65	125.7 335.625	118.7 (CTAF) L 257.9 348.6	121.9 348.6	122.95







CATEGORY	A	B	C	D
LPV DA	241-1 203 (200-1)			
LNAV/VNAV DA	460-1¼ 422 (500-1¼)			
LNAV MDA	460-1 422 (500-1)		460-1¼ 422 (500-1¼)	
CIRCLING	520-1 478 (500-1)	540-1 498 (500-1)	760-2 718 (800-2)	780-2¼ 738 (800-2¼)

NE-3, 26 NOV 2026 to 24 DEC 2026