YIGO, GUAM I, GUAM

TACAN Z RWY 24L

TACAN UAM Chan **54**	APCH CRS **256°**	Rwy ldg **11,199** TDZE **607** Arpt Elev **617**

(USAF) ANDERSEN AFB (PGUA)

RADAR or DME required

* When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 50, vis to 1 mile.
** Circling not authorized NW of Rwy 6L-24R.


SALS (A2)

MISSED APPROACH: Climb to 1100, then climbing left turn to 3000 to intercept UAM R-076 to WELKU and hold.

ATIS	GUAM APP CON/DEP CON	TOWER	GND CON
118.175 254.325	**119.8 269.0**	**126.2 233.7**	**121.7 275.8**

CAUTION: Environmentally Sensitive Area Flights along Andersen cliff line restricted to 1000' AGL or above.

All touchdown zones have a 1.0% down slope.



CATEGORY	A	B	C	D	E
S-24L*	940/40	333 (400-¾)	940/45	333	(400-⅞)
CIRCLING**	1060-1 443 (500-1)	1080-1 463 (500-1)	1240-1¾ 623 (700-1¾)	1240-2 623 (700-2)	1240-2¼ 623 (700-2¼)

HIRL all rwys

PAC, 29 OCT 2026 to 24 DEC 2026

PAC, 29 OCT 2026 to 24 DEC 2026