LOC RWY 25


CAPITAL CITY (FFT)

LOC/DME I-FFT	APP CRS	Rwy Ldg	5506
109.95	249°	TDZE	790
Chan 36 (Y)		Apt Elev	812

Rwy 25 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Lexington altimeter setting and increase all MDA 80 feet. Increase S-25 Cats C/D visibility to 1½ mile and Circling Cat C and D visibility ¼ mile.

MISSED APPROACH: Climb to 3100 then left turn direct HYK VOR/DME and hold.

ASOS	LEXINGTON APP CON	CLNC DEL	UNICOM
119.275	120.75 298.9	118.65	122.8 (CTAF)




MIRL Rwy 7-25

REIL Rwys 7 and 25

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38



CATEGORY	A	B	C	D
S-25	1280-1	490 (500-1)	1280-1⅜	490 (500-1⅜)
CIRCLING	1280-1 468 (500-1)	1380-1 568 (600-1)	1440-1¾ 628 (700-1¾)	1440-2 628 (700-2)

SE-1, 26 NOV 2026 to 24 DEC 2026
SE-1, 26 NOV 2026 to 24 DEC 2026