ILS or LOC RWY 35

ACADIANA RGNL (ARA)

LOC/DME I-ARA	APP CRS	Rwy Ldg	8002
108.9	348°	TDZE	21
Chan 26		Apt Elev	24

DME required for procedure entry. DME required for LOC only.

Circling NA to Rwys 17W and 35W. For inop ALS increase S-ILS 35 Cat E visibility to ¾ SM and S-LOC 35 Cats C/D/E visibility to 1 ⅛ SM.

MALSR

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 on heading 080° and LFT R-114 to CLYNT INT/LFT 18.8 DME and hold.

ASOS	LAFAYETTE APP CON★	ACADIANA TOWER★	GND CON	UNICOM
133.325	121.1 268.7	125.0 (CTAF) L 239.3	121.7	122.95

LULEW
LSU 27.7

LAFAYETTE
109.8 LFT
Chan 35

3000 to PILYI
156° (24.4)

116.5 LSU
Chan 112

R-114

R-211

Procedure NA for arrival on LFT VORTAC airway radials 092 CW 114.

CLYNT
LFT 18.8

294°
114°

LOCALIZER 108.9
I-ARA
Chan 26

119±

UXYAP
I-ARA 4

139

324

ISUCE
I-ARA 6.7

MSA LFT 25 NM
180°
2900
2100
360°

1700
(8)
348°

(IF/IAF)
PILYI
I-ARA 14.7
LFT 24.4

ALTERNATE MISSED APCH FIX
116.5 LSU
Chan 112

LULEW
LSU 27.7

221°
041°
R-221

1 min
348°
168°

HOLD
4500
2000

ELEV 24 D TDZE 21

17
8002 X 200
TWR
35
348°
HIRL Rwy 17-35 L

800	2000	LFT	CLYNT
	hdg 080°	R-114	△

*LOC only.

ISUCE
I-ARA 6.7

PILYI
I-ARA 14.7
One Minute Holding Pattern

168° 4500
348° 2000

1700

348°

I-ARA 1.6

*I-ARA 2.6

UXYAP
I-ARA 4

480*

1700

GS 3.00°
TCH 51

1 NM 1.4 NM 2.7 NM 8 NM

CATEGORY	A	B	C	D	E
S-ILS 35	221-½ 200 (200-½)				
S-LOC 35	440-½ 419 (500-½)		440-¾ 419 (500-¾)		
CIRCLING	440-1 416 (500-1)	480-1 456 (500-1)	600-1½ 576 (600-1½)	680-2 656 (700-2)	900-3 876 (900-3)

SC-4, 26 NOV 2026 to 24 DEC 2026
SC-4, 26 NOV 2026 to 24 DEC 2026