ILS or LOC RWY 4

CLOVIS RGNL (CVN)

LOC/DME I-CVN	APP CRS	Rwy Ldg	7200
108.9	037°	TDZE	4205
Chan 26		Apt Elev	4216


DME required.


Circling NA to Rwys 8 and 26.
For inop ALS, increase S-LOC 4 Cats C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 4700 then climbing right turn to 6000 direct TXO VORTAC and hold.

AWOS-3PT	CANNON APP CON	UNICOM
135.375	118.425 352.1	122.8 (CTAF) L






CATEGORY	A	B	C	D
S-ILS 4	4405-½	200 (200-½)		
S-LOC 4	4560-½	355 (400-½)	4560-⅝	355 (400-⅝)
CIRCLING	4680-1	464 (500-1)	4700-1½ 484 (500-1½)	4820-2 604 (700-2)

ELEV 4216 TDZE 4205

REIL Rwys 12 and 30 L

MIRL Rwys 4-22 and 12-30 L



FAF to MAP 6.4 NM					
Knots	60	90	120	150	180
Min:Sec	6:24	4:16	3:12	2:34	2:08

SW-1, 26 NOV 2026 to 24 DEC 2026
SW-1, 26 NOV 2026 to 24 DEC 2026