RNAV (GPS) RWY 17

BRUCE CAMPBELL FLD (MBO)


WAAS	APP CRS	Rwy Ldg	4444
CH 69231	174°	TDZE	325
W17A		Apt Elev	325


RNP APCH.

Baro-VNAV and VDP NA when using Jackson-Medgar Wiley Evers Intl altimter setting. Rwy 17 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Jackson-Medgar Wiley Evers Intl altimeter setting and increase all DA 21 feet and all MDA 40 feet, and increase LNAV/VNAV visibility ⅛ SM, and Circling Cats C/D visibility ¼ mile.


MISSED APPROACH: Climb to 1200 then climbing left turn to 2400 direct DUHAB and hold.

AWOS-3PT	JACKSON APP CON ★	CLNC DEL	UNICOM
119.125	123.9 317.7	125.9	122.8 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	600-⅞ 275 (300-⅞)			
LNAV/VNAV DA	832-1⅜ 507 (600-1⅜)			
LNAV MDA	800-1 475 (500-1)		800-1⅜ 475 (500-1⅜)	
CIRCLING	820-1 495 (500-1)	840-1 515 (600-1)	1040-2 715 (800-2)	1040-2¼ 715 (800-2¼)



SC-4, 26 NOV 2026 to 24 DEC 2026
SC-4, 26 NOV 2026 to 24 DEC 2026