LOC/DME I-PGV	APP CRS	Rwy Ldg 6505
110.7	197°	TDZE 25
Chan 44		Apt Elev 26

ILS Y or LOC Y RWY 20


PITT-GREENVILLE (PGV)


T ANA ADF required. VDP NA with Washington altimeter setting. When local altimeter setting not received use Washington altimeter setting and increase S-ILS 20 DA to 298 feet; increase all MDAs 60 feet and S-LOC 20 visibility Cat C/D 1⅛ SM, and Circling visibility Cat D 1¼ SM. For inop ALS when using Washington altimeter setting, increase S-ILS 20 all Cats visibility ⅜ SM, and S-LOC 20 visibility Cat A/B ¼ SM. Inop table does not apply to S-ILS all Cats. Rwy 20 helicopter visibility reduction below ¾ SM NA. For inop ALS, increase S-LOC 20 visibility Cat A/B ¼ SM, Cat C/D ⅜ SM.

MALSR


MISSED APPROACH: Climb to 800 then climbing right turn to 1600 direct AQE NDB and hold.

AWOS-3PT	WASHINGTON CENTER	UNICOM
128.425	123.85 279.65	122.8 (CTAF) L





CATEGORY	A	B	C	D
S-ILS 20	257-¾ 231 (300-¾)			
S-LOC 20	420-¾ 394 (400-¾)			
CIRCLING	600-1 574 (600-1)	620-1 594 (600-1)	700-2 674 (700-2)	800-2½ 774 (800-2½)



FAF to MAP 3.7 NM

Knots	60	90	120	150	180
Min:Sec	3:42	2:28	1:51	1:29	1:14

SE-2, 26 NOV 2026 to 24 DEC 2026
SE-2, 26 NOV 2026 to 24 DEC 2026