RNAV (GPS) RWY 34

ABBEVILLE CHRIS CRUSTA MEML (IYA)


WAAS CH 45823 W34A	APP CRS 337°	Rwy Ldg 5000 / TDZE 15 / Apt Elev 16

RNP APCH.

Baro-VNAV NA when using New Iberia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use New Iberia altimeter setting and increase all DA 27 feet and all MDA 40 feet; increase LNAV/VNAV all Cats visibility ⅛ SM.

MISSED APPROACH: Climb to 2000 direct CIPAG and hold.

AWOS-3PT	LAFAYETTE APP CON ★	GCO	UNICOM
118.875	121.1 268.7	135.075	122.8 (CTAF) L



CATEGORY	A	B	C	D
LPV DA	298-1 283 (300-1)			NA
LNAV/VNAV DA	320-1 305 (400-1)			NA
LNAV MDA	580-1 565 (600-1)		580-1⅛ 565 (600-1⅛)	NA
CIRCLING	580-1 564 (600-1)	600-1 584 (600-1)	700-2 684 (700-2)	NA

SC-4, 26 NOV 2026 to 24 DEC 2026
SC-4, 26 NOV 2026 to 24 DEC 2026