
BEAVY NINE DEPARTURE (RNAV)

CHARLOTTE DEP CON
128.325 307.8
AWOS-3P
118.175
CLNC DEL
127.35


RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TOP ALTITUDE: 3000



TAKEOFF MINIMUMS
Rwy 2: Standard.
Rwy 20: 400-2¾ or standard with minimum climb of 203'/NM to 1300, or alternatively, with standard takeoff minimums and a normal 200'/NM climb gradient, takeoff must occur no later than 1300' prior to DER.

NOTE: Turbojet only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or Charlotte CLNC DEL.
NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on assigned heading for vectors to UGANG, thence. . .
TAKEOFF RUNWAY 20: Climb on heading 202° to 1700 before turning right for vectors to UGANG, thence. . .

. . .on track 196° to BEAVY. Then on assigned transition. Maintain 3000, expect filed altitude 10 minutes after departure.

GANDT TRANSITION (BEAVY9.GANDT)
JENDO TRANSITION (BEAVY9.JENDO)

SE-2, 26 NOV 2026 to 24 DEC 2026
SE-2, 26 NOV 2026 to 24 DEC 2026