APP CRS	Rwy Idg	4239
054°	TDZE	821
	Apt Elev	833

RNAV (GPS) RWY 5
WATERTOWN MUNI (RYV)

RNP APCH.

T Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Dodge County altimeter setting and increase all MDAs 60 feet, increase LNAV Cat C visibility ⅛ SM. Circling Rwy 23 NA at night.

MISSED APPROACH: Climb to 3000 direct IJEMI and left turn on 019° track to WIGOR and hold.

AWOS-3	MADISON APP CON ★	UNICOM
119.975	119.15 343.7	122.8 (CTAF) L

MISSED APCH FIX
WIGOR
070°
250°
4 NM

1441
1361
1220
019°
IJEMI
1360
1020±
RW05
1158
1039±

Procedure NA for arrivals on MSN VORTAC airway radials 031 CW 089.

MADISON MSN
3000
099°
(14.3)

(IAF) VECUY
3000
144°
(5)
(FAF) IJITY
2500
054°
(7)
(IF) LUNGS
3000
324°
(5)
(IAF) UDOCA


MSA RW05 25 NM
2700

Procedure NA for arrivals on JVL VOR/DME airway radials 044 CW 073.

3000
022°
(27.1)
JANESVILLE JVL

ELEV 833 D TDZE 821

2801 X 75
0.4% UP
4429 X 75
054°



CATEGORY	A	B	C	D
LNAV MDA	1440-1 619 (700-1)		1440-1¾ 619 (700-1¾)	1440-2 619 (700-2)
CIRCLING	1440-1 607 (700-1)		1720-2¾ 887 (900-2¾)	1720-3 887 (900-3)

REIL Rwys 5 and 23 L
MIRL Rwys 5-23 and 11-29 L

EC-3, 26 NOV 2026 to 24 DEC 2026
EC-3, 26 NOV 2026 to 24 DEC 2026