RNAV (GPS) RWY 32

SMITH CENTER MUNI (K82)


WAAS	APP CRS	Rwy Ldg	4400
CH 63135	323°	TDZE	1800
W32A		Apt Elev	1800

RNP APCH - GPS.

⚠ Baro-VNAV and VDP NA when using CNK altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use CNK altimeter setting: increase LPV DA to 2174 feet; increase LNAV/VNAV DA to 2224 feet and all visibilities ¼ SM; increase all MDAs 180 feet, and Circling all visibilities ½ SM.

MISSED APPROACH: Climb to 3900 direct LAYIP and hold.

AWOS-3PT	MINNEAPOLIS CENTER	UNICOM
118.45	119.4 278.8	122.8 (CTAF) L



CATEGORY	A	B	C	D
LPV DA	2000-1	200 (200-1)	NA	
LNAV/VNAV DA	2050-1	250 (300-1)	NA	
LNAV MDA	2300-1	500 (500-1)	NA	
CIRCLING	2480-1 680 (700-1)	2580-1 780 (800-1)	NA	

NC-2, 26 NOV 2026 to 24 DEC 2026
NC-2, 26 NOV 2026 to 24 DEC 2026