RNAV (GPS) RWY 5

LINCOLN COUNTY RGNL (IPJ)


WAAS	APP CRS	Rwy Ldg	5500
CH 78408	053°	TDZE	878
W05A		Apt Elev	878


RNP APCH.

When local altimeter setting not received, use Charlotte altimeter setting: increase LPV DA to 1395 feet, LNAV/VNAV DA to 1463 feet and visibility LNAV/VNAV ¼ SM; increase all MDAs 80 feet and visibility Cats C and D ¼ SM. Rwy 5 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Charlotte altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C.


MISSED APPROACH: Climb to 3000 direct JIVOM and hold.

AWOS-3	CHARLOTTE APP CON	UNICOM
119.675	134.75 257.2	123.05 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	1332-1⅜ 454 (500-1⅜)			NA
LNAV/VNAV DA	1400-1½ 522 (600-1½)			NA
LNAV MDA	1360-1 482 (500-1)		1360-1⅜ 482 (500-1⅜)	
CIRCLING	1400-1 522 (600-1)	1440-1 562 (600-1)	1660-2¼ 782 (800-2¼)	1660-2½ 782 (800-2½)



SE-2, 26 NOV 2026 to 24 DEC 2026