BOTCH TWO DEPARTURE (RNAV)

(BOTCH2.BOTCH) 14MAY26

FORT WORTH, TEXAS

PEROT FLD/FORT WORTH ALLIANCE (AFW)

TOP ALTITUDE: ASSIGNED BY ATC

RNAV 1 - DME/DME/IRU or GPS required.

RADAR required.

LONE STAR DEP CON
118.1 306.95
ATIS
126.925
CLNC DEL
128.725
GND CON
132.65 306.2
ALLIANCE TOWER
135.15 257.9

MSA AFW 25 NM
4000

HUDAD
9000 *3000 291° (66)
MUTEE
9000 *3600 291° (27)
PGLET
9000 *2600 308° (16)
HULZE
9000 *3100 285° (37)
HRPER
9000 *3000 288° (69)
DBLSS
9000 *2800 288° (27)
TYGGR
9000 *2500 287° (13)
BRHMA
9000 *4000 282° (75)
KATZZ
9000 *3500 282° (71)
RUFFS
9000 *2800 283° (26)
9000 *2500 256° (12)
ROOOO
9000 *2500 232° (15)
BOTCH
13000
270° (13)
DEMII
5000
1223
155°
346°
166°
153°
1223
N
ALIAN
9000 *3200 268° (51)
FUMED
9000 *3100 268° (25)
LYNDE
9000 *3300 262° (56)
9000 *3100 262° (25)
RBBIT
WSTEX
9000 *4100 263° (50)
CIKAN
9000 *3700 251° (33)
DOSXX

TAKEOFF MINIMUMS
Rwys 34L/R: Standard.
Rwys 16L: 300-2¼ or standard with minimum climb of 220′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 1900′ prior to DER.
Rwys 16R: 300-2¼ or standard with minimum climb of 225′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 2000′ prior to DER.

NOTE: ALIAN Transition: ATC assigned only.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

(BOTCH2.BOTCH) 26134

BOTCH TWO DEPARTURE (RNAV)

AL-6918 (FAA)

PEROT FLD/FORT WORTH ALLIANCE (AFW)

FORT WORTH, TEXAS