TEXOMA FIVE DEPARTURE

LONE STAR DEP CON
118.1 306.95
ATIS
126.925
CLNC DEL
128.725
GND CON
132.65 306.2
ALLIANCE TOWER
135.15 257.9

TOP ALTITUDE: ASSIGNED BY ATC

RADAR and DME required.

TULSA
114.4 TUL
Chan 91

WILL ROGERS
114.1 IRW
Chan 88

OKMULGEE
114.9 OKM
Chan 96

ROLLS

DECKK

NOOGY

MRMAC

ZEMMA

EAKER

ARDMORE
116.7 ADM
Chan 114

BONHAM
114.6 BYP
Chan 93

LOWGN

BLECO

GRABE

RANGER
115.7 FUZ
Chan 104

R-277
R-145
R-144
R-212
R-346
R-201
R-196
R-071
R-179
R-256

13000 *3000 021° (124)
4400 *2900 324° (30)
15000 *4500 303° (85)
10000 *2700 360° (3)
11000 *3400 016° (90)
15000 *2900 303° (60)
11000 *2900 325° (66)
9000 *2900 360° (56)
11000 *3700 012° (55)
4000 *2600 359° (46)
4000 *2200 348° (34)
4000 *2700 360° (34)
4000 *3200 012° (35)

MSA FUZ 25 NM
2700
3600
050°
310°

166°
1100

TAKEOFF MINIMUMS
Rwys 34L/R: Standard.
Rwy 16L: 300-2¼ or standard with minimum climb of 220′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 1900′ prior to DER.
Rwy 16R: 300-2¼ or standard with minimum climb of 225′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 2000′ prior to DER.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SC-2, 26 NOV 2026 to 24 DEC 2026