WORTH ONE DEPARTURE

(WORTH1.TTT) 25JAN24

FORT WORTH, TEXAS

PEROT FLD/FORT WORTH ALLIANCE (AFW)

WORTH ONE DEPARTURE

(WORTH1.TTT) 26246

FORT WORTH, TEXAS

PEROT FLD/FORT WORTH ALLIANCE (AFW)

AL-6918 (FAA)

RADAR and DME required.

TOP ALTITUDE: ASSIGNED BY ATC

LONE STAR DEP CON
118.1 306.95
ATIS
126.925
CLNC DEL
128.725
GND CON
132.65 306.2
ALLIANCE TOWER
135.15 257.9

PANHANDLE
116.6 PNH
Chan 113

CHILDRESS
117.0 CDS
Chan 117

WICHITA FALLS
112.7 SPS
Chan 74

TEXICO
112.2 TXO
Chan 59

LUBBOCK
109.2 LBB
Chan 29

CORONA
115.5 CNX
Chan 102

ABILENE
113.7 ABI
Chan 84

MILLSAP
117.7 MQP
Chan 124

MAVERICK
113.1 TTT
Chan 78

SCABI

FERRA

PODDE

R-118 V114 5300 297° (87)

R-127 *14000 *3200 307° (61)

R-233

R-124 5900 305° (66)

V62

R-088 FL180 272° *9300 (192)

R-114 *14000 *4800 296° (127)

V62

V66 3700 253° (96)

R-071

R-081 3000 261° (13)

129 *14000 *3000 285° (92)

4000 *2400 285° (37)

3500 *2800 250° (36)

166° 1100

N

MSA TTT 25 NM
2700
090° 270°
3600

NOTE: PODDE Transition: ATC assigned.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

TAKEOFF MINIMUMS

Rwys 34L/R: Standard.

Rwy 16L: 300-2 ¼ or standard with minimum climb of 220′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 1900′ prior to DER.

Rwy 16R: 300-2 ¼ or standard with minimum climb of 225′/NM to 1100, or alternatively, with standard takeoff minimums and a normal 200′/NM climb gradient, takeoff must occur no later than 2000′ prior to DER.