RNAV (GPS) RWY 17

MARION (C17)


WAAS	APP CRS	Rwy Idg	3532
CH 52102	172°	TDZE	861
W17A		Apt Elev	861


RNP APCH - GPS.

Baro-VNAV NA. Straight-in Rwy 17, NA at night. Circling NA for Cat B west of Rwy 17/35. Use The Eastern Iowa altimeter setting; when not received, use Monticello Rgnl altimeter setting: increase LPV DA to 1162; increase LNAV/VNAV DA to 1670; increase all MDAs 40 feet. For uncompensated Baro-VNAV system, LNAV/VNAV NA below -6°C or above 54°C. Rwy 17, helicopter visibility reduction below 1 SM NA.


MISSED APPROACH: Climb to 1400 then climbing left turn to 2600 direct HENCH and hold.

CID ASOS	CEDAR RAPIDS APP CON ★	UNICOM
124.15	134.05 266.8	122.7 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	1140-1 279 (300-1)		NA	
LNAV/VNAV DA	1648-2½ 787 (800-2½)		NA	
LNAV MDA	1560-1 699 (700-1)		NA	
CIRCLING	1560-1 699 (700-1)	1620-1 759 (800-1)	NA	



NC-3, 26 NOV 2026 to 24 DEC 2026
NC-3, 26 NOV 2026 to 24 DEC 2026